NSN 5962-01-124-8349

Digital Microcircuit - Page 1 of 1



View Online at https://aerobs n/nen/5062-01-124-8340

View Online at https://aerobasegroup.com/nsn/5962-01-124-8349
Body Length:
Between 0.715 inches and 0.740 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.120 inches and 0.160 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
4920-01-084-2649 22680
Features Provided:
Low power and high noise and w/buffered output
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
16.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
16152-40-15957 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.

).; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0