## NSN 5962-01-124-9253

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-124-9253

View Online at https://aerobasegroup.com/nsn/5962-01-124-9253
Body Length:
Between 0.750 inches and 0.780 inches
Body Width:
Between 0.245 inches and 0.275 inches
Body Height:
Between 0.140 inches and 0.160 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
4920-01-054-8585 81755
Features Provided:
Hermetically sealed and monolithic and fast settling
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
8 input
Design Function And Quantity:
1 converter, digital to analog
Terminal Surface Treatment:
Gold or solder or tin
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
16340-62-00005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0