

View Online at <https://aerobasegroup.com/nsn/5962-01-124-9259>

Body Length:

Between 0.750 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.295 inches

Body Height:

0.180 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

4920-01-054-8585 81755

Features Provided:

Burn in, mil-std-883, class b and hermetically sealed and w/common clock

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

4 latch

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 18.5 volts power source

Time Rating Per Characteristic:

440.00 nanoseconds propagation delay time, low to high level output and 440.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0