NSN 5962-01-125-4602

Linear Microcircuit - Page 1 of 1



962-01-125-4602

| View Online at https://aerobasegroup.com/nsn/5 |
|------------------------------------------------|
| Body Length: |
| Between 0.745 inches and 0.755 inches |
| Body Width: |
| Between 0.245 inches and 0.252 inches |
| Body Height: |
| Between 0.115 inches and 0.125 inches |
| Maximum Power Dissipation Rating: |
| 400.0 milliwatts |
| Operating Tempurature Range: |
| -40.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Temperature compensated and dynamic |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 2 channel |
| Design Function And Quantity: |
| 1 expander |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 18.0 volts power source |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0