# NSN 5962-01-126-3177



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-126-3177 **Body Length:** 1.000 inches **Body Width:** Between 0.220 inches and 0.300 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 517.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Flight ref 76301 **Features Provided:** Hermetically sealed and w/common clear and w/common clock and monolithic and positive edge triggered **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 8 flip-flop, d-type **Terminal Surface Treatment:** Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

# **Time Rating Per Chacteristic:**

40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

07187-4032510 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

20 printed circuit

## Shelf Life:

N/a

#### **Unit Of Measure:**

#### **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-126-3177

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0