## NSN 5962-01-126-4630

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-126-4630

View Offline at https://defobasegroup.com/hsh/0302-01-120-4000
Body Length:
Between 0.250 inches and 0.352 inches
Body Outside Diameter:
0.875 inches
Maximum Power Dissipation Rating:
20.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
1055-01-192-0357 launcher, rocket
Features Provided:
Adjustable and high voltage and monolithic
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 regulator, voltage
Case Outline Source And Designator:
To-3 joint electron device engineering council
Current Rating Per Characteristic:
1.50 amperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
40.00 volts input/output differential
Special Features:
Flange mounted
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
2 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5962-01-126-4630

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0