# NSN 5962-01-126-4630

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-126-4630

## **Body Length:**

Between 0.250 inches and 0.352 inches

## **Body Outside Diameter:**

0.875 inches

## **Maximum Power Dissipation Rating:**

20.0 watts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **End Application:**

1055-01-192-0357 launcher, rocket

## Features Provided:

Adjustable and high voltage and monolithic

## Inclosure Material:

Metal

## Inclosure Configuration:

Can

## Input Circuit Pattern:

1 input

## **Design Function And Quantity:**

1 regulator, voltage

# Case Outline Source And Designator:

To-3 joint electron device engineering council

# **Current Rating Per Characteristic:**

1.50 amperes average forward current averaged over a full 60-hz cycle not applicable

## **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

40.00 volts input/output differential

## **Special Features:**

Flange mounted

## Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# Terminal Type And Quantity:

2 pin

# Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# NSN 5962-01-126-4630

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

