NSN 5962-01-126-9903

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-126-9903 **Body Length:** Between 0.750 inches and 0.820 inches **Body Width:** Between 0.300 inches and 0.320 inches **Body Height:** Between 0.095 inches and 0.105 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Circuit card fscm 16331 **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and compatible cmos and compatible dtl and low power **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 2 gate, analog **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -22.0 volts power source and 22.0 volts power source **Time Rating Per Chacteristic:** 400.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

A458a0

Yes - demil/mli