

View Online at <https://aerobasegroup.com/nsn/5962-01-127-6232>

Body Length:

0.185 inches

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

680.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Nimitz class cvn; spruance class dd (963); kieded class ddg; viriginia class cgn (41); los angeles class ssn (688); ticonderoga class ctg (47); support equipment, mx peacekeeper missile; sturgeon vclass ssn (637); forrestal class cv; communications system an/wsc-3; sirius class t-a fs 8; hayes class t-ag 195; t-akr 310 class; austin ship class lpd-4 amphibious transport docks

Features Provided:

Hermetically sealed and monolithic and high voltage

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Case Outline Source And Designator:

A-1 mil-m-38510

Current Rating Per Characteristic:

4.00 milliamperes forward current, peak total value not applicable

Terminal Surface Treatment:

Solder

Test Data Document:

14933-78003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0