## NSN 5962-01-127-6238

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-127-6238

**Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+110.0 degrees celsius Storage Tempurature Range: -60.0/+150.0 degrees celsius **End Application:** 1055-01-092-0596 18876 **Features Provided:** Hermetically sealed and monolithic and w/clock **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 11 input **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 200.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Ram **Memory Capacity:** Unknown **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 printed circuit

81349-mil-m-38510/240 government specification

**Specification Data:** 

## NSN 5962-01-127-6238

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0