## NSN 5962-01-127-8855

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-127-8855

| Body Length:   |
|--|
| 0.400 inches   |
| Body Width:  |
| 0.275 inches   |
| Body Height:   |
| 0.065 inches   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| F16aircombfit 81755; wsd: aircraft, phantom f-4; aircraft, f-16  |
| Features Provided:   |
| Burn in and bipolar and w/open collector and monolithic and programmed and w/enable and positive outputs                           |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Flat pack  |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| 10 input   |
| Criticality Code Justification:  |
| Feat   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| -1.5 volts power source and 5.5 volts power source   |
| Memory Device Type:  |
| Rom  |
| Memory Capacity:   |
| Unknown  |
| Special Features:  |
| Weapon system essential  |
| Test Data Document:  |
| 88818-a574a025 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                  |
| Terminal Type And Quantity:  |
| 16 flat leads  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
|  |

## NSN 5962-01-127-8855

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

