## NSN 5962-01-128-1229

Digital Microcircuit - Page 1 of 1

No Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-128-1229 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and resettable and 3-state output **Inclosure Material:** Ceramic or glass or metal **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 3 input **Design Function And Quantity:** 4 latch, nor, r/s **Case Outline Source And Designator:** F-5 mil-m-38510 **Time Rating Per Chacteristic:** 350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:** Demilitarization: