

View Online at <https://aerobasegroup.com/nsn/5962-01-128-1505>

Body Length:

1.200 inches

Body Width:

0.590 inches

Body Height:

0.143 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

-55.0 to 125.0 degrees celsius

Storage Temperature Range:

-55.0 to 125.0 degrees celsius

End Application:

An/upd-4 enmt fscm 99696

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and low power and bipolar and unipolar

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

14 input

Design Function And Quantity:

1 converter, digital to analog

Current Rating Per Characteristic:

30.00 milliamperes supply

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-18.0 volts power source and 18.0 volts power source

Time Rating Per Characteristic:

300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0