NSN 5962-01-128-1512

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-128-1512

| Body Length: | |
|---|--|
| 1.725 inches | |
| Body Width: | |
| 1.220 inches | |
| Body Height: | |
| 0.190 inches | |
| Maximum Power Dissipation Rating: | |
| 1.3 watts | |
| Operating Tempurature Range: | |
| -60.0/+115.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| End Application: | |
| Ins fscm 76301 | |
| Features Provided: | |
| Hermetically sealed and hybrid and programmable and resettable and w/strobe | |
| Inclosure Material: | |
| Ceramic and glass | |
| Inclosure Configuration: | |
| Dual-in-line | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| Input Circuit Pattern: | |
| 20 input | |
| Terminal Surface Treatment: | |
| Solder | |
| Product Name: | |
| Serial data bus single | |
| Voltage Rating And Type Per Characteristic: | |
| 5.5 volts power source | |
| Test Data Document: | |
| 06481-371439 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; | |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) | |
| Terminal Type And Quantity: | |
| 62 printed circuit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| A458a0 | |
| | |