NSN 5962-01-128-3894

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-128-3894

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.240 inches and 0.260 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Display grp 76301 |
| Features Provided: |
| Hermetically sealed and monolithic and high speed |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| Dual 2 input |
| Design Function And Quantity: |
| 2 comparator |
| Case Outline Source And Designator: |
| T0-5 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -15.0 volts power source and 15.0 volts power source |
| Test Data Document: |
| 09344-pc73573 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 10 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| |