NSN 5962-01-128-3906

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-128-3906

View Online at https://aerobasegroup.com/nsn/5962-01-128-3906
Body Length:
Between 0.245 inches and 0.260 inches
Body Width:
Between 0.245 inches and 0.260 inches
Body Height:
Between 0.040 inches and 0.060 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Data link 76301
Features Provided:
Hermetically sealed and high speed and schottky and w/open collector and 3-state output
Inclosure Material:
Ceramic
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 2 wide 2 input
Design Function And Quantity:
2 gate, and-or invert
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.2 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
5.50 nanoseconds propagation delay time, low to high level output and 5.50 nanoseconds propagation delay time, high to low level output
Test Data Document:
13499-351-1992 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli

Fiig:

A458a0