## NSN 5962-01-128-3910

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-128-3910

Body Length: Between 0.750 inches and 0.785 inches Body Width: Between 0.245 inches and 0.271 inches Body Height: Between 0.140 inches and 0.185 inches Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 6625-01-098-6764 Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Between 0.245 inches and 0.271 inches Body Height: Between 0.140 inches and 0.185 inches Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 6625-01-098-6764 Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Between 0.245 inches and 0.271 inches  Body Height:  Between 0.140 inches and 0.185 inches  Storage Tempurature Range: -65.0/+150.0 degrees celsius  End Application: 6625-01-098-6764  Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input  Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.2 volts power source  Terminal Type And Quantity:	
Body Height:  Between 0.140 inches and 0.185 inches  Storage Tempurature Range: -65.0/+150.0 degrees celsius  End Application: 6625-01-098-6764  Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Between 0.140 inches and 0.185 inches  Storage Tempurature Range: -65.0/+150.0 degrees celsius  End Application: 6625-01-098-6764  Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Storage Tempurature Range: -65.0/+150.0 degrees celsius  End Application: 6625-01-098-6764  Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
-65.0/+150.0 degrees celsius  End Application: 6625-01-098-6764  Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
End Application: 6625-01-098-6764  Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Features Provided: Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Features Provided:  Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material:  Ceramic and glass Inclosure Configuration:  Dual-in-line  Output Logic Form:  Emitter-coupled logic Input Circuit Pattern:  5 input  Design Function And Quantity:  1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  5.2 volts power source  Terminal Type And Quantity:	
Hermetically sealed and monolithic and high speed and asynchronous and w/enable and w/clear and complementary ou Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Ceramic and glass Inclosure Configuration:  Dual-in-line Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	outs
Inclosure Configuration:  Dual-in-line  Output Logic Form:  Emitter-coupled logic  Input Circuit Pattern:  5 input  Design Function And Quantity:  1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  5.2 volts power source  Terminal Type And Quantity:	
Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Output Logic Form: Emitter-coupled logic Input Circuit Pattern: 5 input Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Input Circuit Pattern: 5 input  Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.2 volts power source  Terminal Type And Quantity:	
Input Circuit Pattern: 5 input  Design Function And Quantity: 1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.2 volts power source  Terminal Type And Quantity:	
Design Function And Quantity:  1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  5.2 volts power source  Terminal Type And Quantity:	
Design Function And Quantity:  1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  5.2 volts power source  Terminal Type And Quantity:	
1 flip-flop, d-type, master slave, clocked  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.2 volts power source  Terminal Type And Quantity:	
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
Solder  Voltage Rating And Type Per Characteristic:  5.2 volts power source  Terminal Type And Quantity:	
Voltage Rating And Type Per Characteristic: 5.2 volts power source Terminal Type And Quantity:	
5.2 volts power source  Terminal Type And Quantity:	
Terminal Type And Quantity:	
40 minuted disputit	
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	