# NSN 5962-01-128-9281

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-128-9281

# **Body Length:**

Between 0.337 inches and 0.350 inches

# **Body Width:**

Between 0.235 inches and 0.265 inches

# **Body Height:**

Between 0.050 inches and 0.080 inches

# **Maximum Power Dissipation Rating:**

6.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/totem pole output and low power

#### **Inclosure Material:**

# Ceramic and glass

Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Hex 1 input

#### **Design Function And Quantity:**

6 inverter

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.5 volts power source

#### Time Rating Per Chacteristic:

60.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

14 flat leads

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0