NSN 5962-01-128-9749

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-128-9749 **Body Length:** 0.785 inches **Body Width:** 0.280 inches **Body Height:** 0.170 inches **Maximum Power Dissipation Rating:** 880.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Hsd 76301 **Features Provided:** Hermetically sealed and negative outputs and positive outputs and high slew rate **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -15.0 volts power source and 15.0 volts power source **Time Rating Per Chacteristic:** 38.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 55972-2800573 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli