NSN 5962-01-128-9759

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-128-9759

| Body Length: |
|---|
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.290 inches |
| Body Height: |
| 0.185 inches |
| Maximum Power Dissipation Rating: |
| 150.0 milliwatts |
| Operating Tempurature Range: |
| 55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| 65.0/+150.0 degrees celsius |
| End Application: |
| Display grp 76301 |
| Features Provided: |
| Burn in and hermetically sealed and w/buffered output and medium speed and positive outputs |
| nclosure Material: |
| Ceramic |
| nclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| nput Circuit Pattern: |
| Dual 1 input |
| Design Function And Quantity: |
| 2 multivibrator, voltage controlled |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Test Data Document: |
| 09344-pc73562 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A458a0