NSN 5962-01-129-1277

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-129-1277 **Body Length:** 1.573 inches **Body Width:** 1.050 inches **Body Height:** Between 0.250 inches and 0.450 inches **Maximum Power Dissipation Rating:** 20.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Surface minesweeping systems; forrestal class cv; sturgeon class ssn (637); ticonderoga class cg (47); computer display set, an/uyq-2 (v); radio transmitter set, an/urt-23 (rts); virginia class cgn (41); spruance class dd 9963); los angeles class ssn (688) **Features Provided:** Hermetically sealed and adjustable and high performance **Inclosure Material:** Metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 1 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 regulator, voltage **Case Outline Source And Designator:** To-3 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 40.0 volts power source **Special Features:** Weapon system essential **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 3 pin

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-129-1277

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0