NSN 5962-01-129-1899

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-129-1899

| Body Outside Diameter: |
|---|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.160 inches and 0.220 inches |
| Maximum Power Dissipation Rating: |
| 300.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Display grp 76301 |
| Features Provided: |
| Hermetically sealed and negative outputs and positive outputs |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 reference, voltage, analog |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 20.0 volts power source |
| Test Data Document: |
| 09344-pc73563 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |