

View Online at <https://aerobasegroup.com/nsn/5962-01-129-6427>

Overall Height:

0.400 inches

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

739.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and programmed and schottky and 3-state output and w/enable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Case Outline Source And Designator:

D-2 mil-m-38510

Voltage Rating And Type Per Characteristic:

7.0 volts input

Time Rating Per Characteristic:

80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Prom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0