NSN 5962-01-129-7255

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-129-7255

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

350.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and w/field effect transistor switch

Inclosure Material:

Metal

Inclosure Configuration:

Inclos Can

Input Circuit Pattern:

2 channel

Design Function And Quantity:

2 switch, analog

Case Outline Source And Designator:

A-2 mil-m-38510

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-22.0 volts power source and 22.0 volts power source

Time Rating Per Chacteristic:

200.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 pin

Specification Data:

81349-mil-m-38510/111 government specification

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-129-7255

Linear Microcircuit - Page 2 of 2

Demilitarization:

No

Fiig:

A458a0

