NSN 5962-01-129-7924

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-129-7924

| view Offilite at https://aerobasegroup.com/hsi//0302-01-123-732-4 |
|--|
| Body Length: |
| 0.440 inches |
| Body Width: |
| Between 0.245 inches and 0.285 inches |
| Body Height: |
| Between 0.045 inches and 0.085 inches |
| Maximum Power Dissipation Rating: |
| 209.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and synchronous and w/enable and w/clear and edge triggered |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 13 input |
| Case Outline Source And Designator: |
| F-5 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -1.5 volts power source and 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 52.00 nanoseconds propagation delay time, low to high level output and 52.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 14933-80017 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 16 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig: A458a0

Yes - demil/mli