# NSN 5962-01-130-0056

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-130-0056

# **Body Length:**

Between 0.755 inches and 0.785 inches

# **Body Width:**

Between 0.245 inches and 0.271 inches

# **Body Height:**

0.185 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

B-52g/h wst 36378

## Features Provided:

Hermetically sealed and burn in and w/common enable and w/resistor and complementary outputs and high speed

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Emitter-coupled logic

## Input Circuit Pattern:

9 input

#### **Design Function And Quantity:**

4 gate, exclusive or

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-8.0 volts power source

## Time Rating Per Chacteristic:

4.00 nanoseconds propagation delay time, low to high level output and 4.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

## Fiig:

A458a0