

View Online at <https://aerobasegroup.com/nsn/5962-01-130-2001>

Body Length:

0.896 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5810-01-082-8411 49671

Features Provided:

Hermetically sealed and burn in and monolithic and medium speed and high voltage

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

4 gate, and-or

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

20.5 volts power source

Time Rating Per Characteristic:

180.00 nanoseconds propagation delay time, low to high level output and 180.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

98230-0n300708 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0