NSN 5962-01-130-3727

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-130-3727
Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.135 inches and 0.150 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Gun, 30mm type gpu5a fscm 05606
Features Provided:
Hermetically sealed and monolithic and positive outputs and resettable and w/enable and w/strobe and w/storage
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
14 input
Design Function And Quantity:
2 latch
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.5 volts power source
Time Rating Per Chacteristic:
440.00 nanoseconds propagation delay time, low to high level output and 440.00 nanoseconds propagation delay time, high to low leve
output
Test Data Document:
05606-172a1328 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-130-3727

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0