## NSN 5962-01-130-4016



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-130-4016 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Gun, 30mm type gpu5a fscm 05606 **Features Provided:** Hermetically sealed and monolithic and positive outputs and low power **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 6 channel **Design Function And Quantity:** 1 converter, analog to digital **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 18.5 volts power source **Time Rating Per Chacteristic:** 1100.00 nanoseconds propagation delay time, low to high level output and 1300.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 05606-172a1339 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 

16 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0