## NSN 5962-01-130-5604

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-130-5604

<b>Body Outside Diameter:</b>
Between 0.335 inches and 0.370 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
630.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Features Provided:
Hermetically sealed
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
3 input
Design Function And Quantity:
Design Function And Quantity.
1 amplifier, operational, general purpose
-
1 amplifier, operational, general purpose
1 amplifier, operational, general purpose  Terminal Surface Treatment:
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity:
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity:  8 pin
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity:  8 pin  Shelf Life:
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:
1 amplifier, operational, general purpose  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity: 8 pin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
1 amplifier, operational, general purpose  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -36.0 volts power source and 36.0 volts power source  Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli