NSN 5962-01-130-8649

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-130-8649

| view Offilite at https://aerobasegroup.com/nish/0302-01-130-00 1 3 |
|---|
| Body Length: |
| Between 1.439 inches and 1.573 inches |
| Body Width: |
| Between 0.990 inches and 1.050 inches |
| Body Height: |
| Between 0.250 inches and 0.450 inches |
| Maximum Power Dissipation Rating: |
| 30.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Display grp 76301 |
| Features Provided: |
| Hermetically sealed and negative outputs and positive outputs |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 1 input |
| Design Function And Quantity: |
| 1 regulator, voltage |
| Case Outline Source And Designator: |
| T0-3 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder or tin |
| Voltage Rating And Type Per Characteristic: |
| 20.0 volts power source |
| Test Data Document: |
| 09344-pc73542 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |