

View Online at <https://aerobasegroup.com/nsn/5962-01-130-8650>

Body Length:

Between 0.770 inches and 0.810 inches

Body Width:

Between 0.280 inches and 0.300 inches

Body Height:

Between 0.060 inches and 0.120 inches

Maximum Power Dissipation Rating:

450.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

B-52g/h wst e/i fscm 36378

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

8 channel

Design Function And Quantity:

1 multiplexer, analog

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-17.0 volts power source and 17.0 volts power source

Time Rating Per Characteristic:

8000.00 nanoseconds propagation delay time, low to high level output and 8000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0