

View Online at <https://aerobasegroup.com/nsn/5962-01-130-8650>

**Body Length:**

Between 0.770 inches and 0.810 inches

**Body Width:**

Between 0.280 inches and 0.300 inches

**Body Height:**

Between 0.060 inches and 0.120 inches

**Maximum Power Dissipation Rating:**

450.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

B-52g/h wst e/i fscm 36378

**Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

8 channel

**Design Function And Quantity:**

1 multiplexer, analog

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-17.0 volts power source and 17.0 volts power source

**Time Rating Per Characteristic:**

8000.00 nanoseconds propagation delay time, low to high level output and 8000.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0