## NSN 5962-01-130-8652



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-130-8652 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1000.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Multi-hull 03950 **Features Provided:** Hermetically sealed and monolithic and w/strobe and 3-state output and w/open collector **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 4 receiver, line **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -7.0 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0