# NSN 5962-01-131-3900

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-131-3900

# **Body Length:**

Between 0.740 inches and 0.870 inches

# **Body Width:**

Between 0.220 inches and 0.310 inches

# **Body Height:**

0.200 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

4920nc399568g 81755

#### **Features Provided:**

Hermetically sealed and high speed and cascadable and presettable and synchronous

#### **Inclosure Material:**

# Ceramic and glass

Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Emitter-coupled logic

# Input Circuit Pattern:

4 input

# **Design Function And Quantity:**

1 counter, binary

# **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 0.0 volts power source

# Time Rating Per Chacteristic:

5.00 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output

#### Test Data Document:

12436-6010469 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

16 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

# Fiig:

A458a0