

View Online at <https://aerobasegroup.com/nsn/5962-01-131-7034>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

600.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

E-3a aircraft 81205

Features Provided:

Hermetically sealed and monolithic and selected item

Inclosure Material:

Metal

Inclosure Configuration:

Can

Output Logic Form:

Metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 1 input

Design Function And Quantity:

2 driver, clock

Time Rating Per Characteristic:

25.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

97942-581r649 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0