NSN 5962-01-131-9302

Memory Microcircuit - Page 1 of 1



| Memory Microcircuit - Page 1 of 1 | Grou |
|--|----------------------|
| View Online at https://aerobasegroup.com/nsn/5962-01-131-9302 | |
| Body Length: | |
| 0.808 inches | |
| Body Width: | |
| 0.294 inches | |
| Body Height: | |
| 0.204 inches | |
| Operating Tempurature Range: | |
| +0.0/+75.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| Features Provided: | |
| Hermetically sealed and w/enable and programmable and bipolar | |
| Inclosure Material: | |
| Ceramic | |
| Inclosure Configuration: | |
| Dual-in-line | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| Input Circuit Pattern: | |
| 10 input | |
| Terminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| 5.5 volts power source | |
| Time Rating Per Chacteristic: | |
| 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay tim | e, high to low level |
| output | |
| Memory Device Type: | |
| Rom | |
| Memory Capacity: | |
| Unknown | |
| Terminal Type And Quantity: | |
| 16 printed circuit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Filg: | |
| A458a0 | |
| | |
| | |