NSN 5962-01-132-5044

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-132-5044

| Body Length: |
|--|
| 0.960 inches |
| Body Width: |
| Between 0.220 inches and 0.310 inches |
| Body Height: |
| 0.185 inches |
| Maximum Power Dissipation Rating: |
| 794.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and burn in and monolithic and positive outputs and bipolar and 3-state output and programmed |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 12 input |
| Case Outline Source And Designator: |
| D-6 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 85.00 nanoseconds delay |
| Memory Device Type: |
| Prom |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 18 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

NSN 5962-01-132-5044

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

