## NSN 5962-01-132-8226

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5062-01-132-8226

View Online at https://aerobasegroup.com/nsn/5962-01-132-8226
Body Length:
0.390 inches
Body Width:
Between 0.235 inches and 0.260 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/field effect transistor switch
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
2 channel
Design Function And Quantity:
2 switch, analog
Case Outline Source And Designator:
F-1 mil-m-38510
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-38510/111 government specification
Shelf Life:
N/a
Unit Of Measure:

Voc domil/mli

Demilitarization:

## NSN 5962-01-132-8226

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0