NSN 5962-01-133-1279

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-133-1279
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Flight set 76301
Features Provided:
Hermetically sealed and monolithic and low power and schottky
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 gate, nor
Case Outline Source And Designator:
D-1 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
89954-283a8757 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
_

Yes - demil/mli

Demilitarization:

NSN 5962-01-133-1279

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0