# NSN 5962-01-133-1911

Digital Microcircuit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5962-01-133-1911



## **Body Length:**

1.060 inches

# Body Width:

Between 0.220 inches and 0.310 inches

# **Body Height:**

Between 0.160 inches and 0.205 inches

# **Maximum Power Dissipation Rating:**

187.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

F/tf-15a aircraft 76301

#### Features Provided:

W/buffered output and w/enable and low power and schottky and 3-state output

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

Transistor-transistor logic

### Input Circuit Pattern:

10 input

#### **Design Function And Quantity:**

1 decoder, three to eight line

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 7.0 volts power source

#### Time Rating Per Chacteristic:

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level

# output

# **Test Data Document:**

07187-4045383 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

20 printed circuit

# Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# **NSN 5962-01-133-1911** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

