## NSN 5962-01-133-7080

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-133-7080 **Body Length:** Between 0.745 inches and 0.755 inches **Body Width:** Between 0.245 inches and 0.252 inches **Body Height:** Between 0.115 inches and 0.125 inches **Maximum Power Dissipation Rating:** 457.0 milliwatts **Operating Tempurature Range:** -0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Monolithic and positive outputs and schottky and w/common enable and 3-state output **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 4 transceiver **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 17.00 nanoseconds propagation delay time, low to high level output and 17.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0