NSN 5962-01-133-9649

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-133-9649

Body Length:
Between 1.445 inches and 1.475 inches
Body Width:
Between 0.515 inches and 0.545 inches
Body Height:
Between 0.160 inches and 0.200 inches
Maximum Power Dissipation Rating:
1200.0 milliwatts
Operating Tempurature Range:
-0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/apy 08783
Features Provided:
Hermetically sealed and high speed and monolithic and dielectric isolated and high performance and w/enable and w/inhibit
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
21 input
Design Function And Quantity:
1 multiplexer, analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-2.0 volts power source and 2.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low leve
output
Terminal Type And Quantity:
28 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: