NSN 5962-01-134-2211

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-134-2211

Body Length: Between 0.740 inches and 0.840 inches Body Width: Between 0.240 inches and 0.260 inches Body Height: Between 0.120 inches and 0.180 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Body Width: Between 0.240 inches and 0.260 inches Body Height: Between 0.120 inches and 0.180 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Between 0.240 inches and 0.260 inches Body Height: Between 0.120 inches and 0.180 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Between 0.120 inches and 0.180 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Between 0.120 inches and 0.180 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
+0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
+0.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
-55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
-55.0/+150.0 degrees celsius End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
End Application: Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Test set 94987 Features Provided: Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Darlington-connected and monolithic and high gain and compatible cmos and compatible dtl Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Inclosure Material: Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Plastic Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 7 input
Dual-in-line Input Circuit Pattern: 7 input
Input Circuit Pattern: 7 input
7 input
Design Function And Quantity:
7 array, darlington transistor
Terminal Surface Treatment:
Tin
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0