NSN 5962-01-135-5488

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-135-5488
Body Length:
Between 1.180 inches and 1.220 inches
Body Width:
Between 0.560 inches and 0.600 inches
Body Height:
Between 0.080 inches and 0.130 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
4920-01-054-8585 81755
Features Provided:
Hermetically sealed and monolithic and programmable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Metal oxide-semiconductor logic
Input Circuit Pattern:
8 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-20.0 volts power source
Time Rating Per Chacteristic:
1000.00 nanoseconds propagation delay time, low to high level output
Memory Device Type:
Rom
Test Data Document:
16340-64-00009 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-135-5488

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0