## NSN 5962-01-135-9771

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-135-9771 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **End Application:** 4920-00-001-5267 81755 **Features Provided:** W/reset and w/clock and positive edge triggered and asynchronous and complementary outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form: Emitter-coupled logic Input Circuit Pattern:** 7 input **Design Function And Quantity:** 1 counter **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -8.0 volts power source **Time Rating Per Chacteristic:** 5.00 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

**Demilitarization:** 

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5962-01-135-9771

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0