NSN 5962-01-137-2326

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-137-2326

view Online at https://aerobasegroup.com/nsn/5962-01-137-2326
Body Length:
Between 1.975 inches and 2.025 inches
Body Width:
Between 0.543 inches and 0.596 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
1000.0 milliwatts
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
End Application:
An/gpn-t4 23259
Features Provided:
Hermetically sealed and 3-state output and w/reset
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
32 input
Design Function And Quantity:
1 control, memory access
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
57230-es52spl68a44 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
40 printed circuit
Shelf Life:
N/a
Unit Of Measure

Demilitarization: Yes - demil/mli

NSN 5962-01-137-2326

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0