NSN 5962-01-137-5418

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-137-5418

Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inches and 0.310 inches	
Body Height:	
Between 0.140 inches and 0.185 inches	
Maximum Power Dissipation Rating:	
450.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and monolithic and compatible cmos and low power	
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Dual-in-line	
Input Circuit Pattern:	
Dual 1 input	
Design Function And Quantity:	
2 switch, analog	
Case Outline Source And Designator:	
D-2 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
4.0 volts power source	
Time Rating Per Chacteristic:	
1600.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level	I
output	
Test Data Document:	
56996-b4009566 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,	
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Terminal Type And Quantity:	
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	