

View Online at <https://aerobasegroup.com/nsn/5962-01-138-0485>

**Body Length:**

0.400 inches

**Body Width:**

0.250 inches

**Body Height:**

0.130 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Tarawa class lha; spruance class dd (963); arleigh burke class ddg; forrestal class cv; kidd class cvn; virginia class cgn (41); wasp class lhd; ticonderoga class cg (47); austin ship class lpd-4 amphibious transport docks

**Features Provided:**

High speed and internally compensated and frequency compensated and w/resistor

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

2 input

**Design Function And Quantity:**

1 amplifier, operational, general purpose

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-20.0 volts power source and 20.0 volts power source

**Terminal Type And Quantity:**

8 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0