NSN 5962-01-138-4156

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-138-4156

Body Length: 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Medium current and high voltage and w/open collector and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 7 channel **Design Function And Quantity:** 7 driver, non-inverting **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 500.00 milliamperes collector **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 95.0 volts absolute output and 30.0 volts absolute input **Capitance Rating Per Characteristic:** 15.00 input picofarads **Time Rating Per Chacteristic:** 1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output **Special Features:** Seven npn darlington pairs configured for cmos or pmos input logic levels of 6v to 15v **Terminal Type And Quantity:**

Shelf Life:

16 printed circuit **Specification Data:**

10138-19341-001 manufacturers specification control

N/a

NSN 5962-01-138-4156

Linear Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0